



DECLARATION OF PERFORMANCE
CE Marking of Thermally toughened glass on Float tinted glass bronze
(Salavatsteklo) – EN 12150-2

№:
170510/6



Product Identifying Code – Type: MG Tempered – Type A

NB: SSV 1694

| Essential Characteristics | AVCP system | Performance | | | | | |
|---|-------------|-------------|-------|-------|-------|-------|-------|
| | | 4 mm | 5 mm | 6 mm | 8 mm | 10 mm | 12 mm |
| Safety in the case of fire | | | | | | | |
| Resistance to fire (EN 13501-2) | 1 | NPD | NPD | NPD | NPD | NPD | NPD |
| Reaction to fire (EN 13501-1) | 3,4 | A1 | A1 | A1 | A1 | NPD | NPD |
| External fire performance | 3,4 | NPD | NPD | NPD | NPD | NPD | NPD |
| Safety in Use | | | | | | | |
| Bullet resistance (EN 1063) | 1 | NPD | NPD | NPD | NPD | NPD | NPD |
| Explosion resistance (EN 13541) | 1 | NPD | NPD | NPD | NPD | NPD | NPD |
| Burglar resistance (EN 356) | 3 | NPD | NPD | NPD | NPD | NPD | NPD |
| Resistance to impact (Pendulum test) (EN 12600) | 3 | 1(C)1 | 1(C)2 | 1(C)2 | 1(C)1 | NPD | NPD |
| Resistance against sudden temperature changes and temperature differentials | 4 | 200°K | 200°K | 200°K | 200°K | NPD | NPD |
| Resistance against wind, snow, permanent and imposed load | 4 | 120 | 120 | 120 | 120 | NPD | NPD |
| Protection against noise | | | | | | | |
| Direct airborne sound reduction (EN 12758): R_w (C, Ctr) | 3 | NPD | NPD | NPD | NPD | NPD | NPD |
| Thermal properties | | | | | | | |
| Declared emissivity (EN 12898) | 3 | NPD | NPD | NPD | NPD | NPD | NPD |
| Thermal property (EN 673): U_g value (W/m^2K) | 3 | NPD | NPD | NPD | NPD | NPD | NPD |
| Radiation properties | | | | | | | |
| Light transmittance / reflectance (EN 410): τ_v / ρ_v / | 3 | 0,60 | NPD | 0,48 | 0,39 | NPD | NPD |
| Solar energy characteristics | | | | | | | |
| Solar direct transmittance / reflectance (EN 410) | 3 | NPD | NPD | NPD | NPD | NPD | NPD |
| Solar Factor (EN 410): g | 3 | NPD | NPD | NPD | NPD | NPD | NPD |
| Durability | | | | | | | |
| | 3 | PASS | PASS | PASS | PASS | PASS | PASS |

